



Ducting & Accessories


Elbow Bend. 150mm to Rectangular. M to F

	Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
			A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
	436626	204 x 60	80	215	195	2.8	4.9	11.6	21	31	41	53	67
	449362	220 x 90	118	226	240	N/A			N/A			N/A	


Elbow Bend. 100mm to Rectangular. F to F

	Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
			A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
	436608	110 x 54	90	115	140	2.1	5.5	14.3	27.2	44.3	69	93	118


Flat Channel connector with Damper

	Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
			A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
	400735	110 x 54	60	115	75	16	17.5	19.5	22	25.5	30.5	36	42


Drop down section F to F

	Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
			A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
	442273	204 x 60	120	220	210	0.2	0.5	1.7	3.6	6.0	9.1	12.4	16.6

Single Air Brick Horizontal (System 60 Air Grille Adaptor is supplied with the Single Air Bricks)

	Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
			A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
	436612	110 x 54 (Terracotta)	65	210	85	3.2	7.8	20.9	39	65	96	128	176
	436611	110 x 54 (Brown)	65	210	85	3.2	7.8	20.9	39	65	96	128	176

Single Air Grille Soldier

	Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
			A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
	438594	204 x 60 (White)	210	65	15	3.3	10	20.6	40	63	92.8	128	168
	468728	204 x 60 (Terracotta)	210	65	15	3.3	10	20.6	40	63	92.8	128	168
	468730	204 x 60 (Brown)	210	65	15	3.3	10	20.6	40	63	92.8	128	168
	468729	204 x 60 (Beige)	210	65	15	3.3	10	20.6	40	63	92.8	128	168