



# Ducting & Accessories

## Round (F) 125mm to Rectangular (F) Adaptor



Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
<b>370127</b>	204 x 60	140	210	213	<1	<1	1.5	2.8	4.5	6.7	9	11.5

## Round (F) 150mm to Rectangular (F) Adaptor




Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate		
		A	B	C	60 l/s	120 l/s	180 l/s
<b>403031</b>	220 x 90	160	225	203	N/A	N/A	N/A

## Short Round (M) 100mm to 110 x 54 (F) Adaptor




Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
<b>455035</b>	110 x 54	60	110	105	1.2	4.3	8.4	20	30.2	43	62	88

## Round Ducting Insulated/Uninsulated



Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
<b>497488</b>	Uninsulated 100 Ø x 1m	100	100	1000	<0.5	<0.5	0.85	1.4	1.8	2.25	2.65	3.1
<b>406873</b>	Insulated 100 Ø* x 2m	200	200	2000	<1	<1	1.7	2.8	3.6	4.5	5.3	6.2
<b>5108250</b>	Uninsulated 100 Ø x 2m	100	100	2000	<1	<1	1.7	2.8	3.6	4.5	5.3	6.2
<b>496155</b>	Uninsulated 120 Ø x 1m	120	120	1000	<0.5	<0.5	<0.5	0.65	0.9	1.2	1.55	1.9
<b>434715</b>	Uninsulated 125 Ø* x 1.5m	125	125	1500	<1	<1	<1	1.3	1.8	2.4	3.1	3.8
<b>406874</b>	Insulated 125 Ø* x 2m	225	225	2000	<1	<1	<1	1.3	1.8	2.4	3.1	3.8
<b>496158</b>	Uninsulated 150 Ø x 1m	150	150	1000	<0.5	<0.5	<0.5	<0.5	0.6	0.8	1	1.25
<b>496159</b>	Uninsulated 150 Ø x 1.5m	150	150	1500	-	-	-	-	-	-	-	-
<b>406875</b>	Insulated 150 Ø* x 2m	265	265	2000	<1	<1	<1	<1	1.2	1.6	2	2.5
<b>5108248</b>	Uninsulated 150 Ø x 2m	150	150	2000	<1	<1	<1	<	1.2	1.6	2	2.5

## Equal Tee Insulated/Uninsulated MMM



Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
<b>406884</b>	Insulated 100 Ø*	290	210	235	vary on installation							
<b>372007</b>	Uninsulated 100 Ø	190	110	135	vary on installation							
<b>406885</b>	Insulated 125 Ø*	310	215	260	vary on installation							
<b>428636</b>	Uninsulated 125 Ø	210	115	160	vary on installation							
<b>406886</b>	Insulated 150 Ø*	335	245	285	vary on installation							
<b>370237</b>	Uninsulated 150 Ø	235	130	177	vary on installation							

\*Minimum insulation wall thickness 25mm. Insulation Thermal Conductivity: 0.04 W/(m.K)