

ELECTRICAL LOCKING

SHEAR MAGNETS

- The AEMSF300 is fire rated to EN1634-1 for 30 & 60 min. timber doors
- A holding force of 2000 lbs for the AEMSF300 is achieved by a combination of the magnetic force and interlocking pins
- The shear magnets can be fitted vertical or horizontal
- Suitable for single or double swing, single or pairs of doors



SHEAR MAGNETS	
AEMSF300	Fire Rated FD60 Mortice Shear Magnet 12/24v Monitored (30mm Wide)
AEM/SHEAR-30	GS705-30 Mortice Shear Magnet 12/24v Monitored (30mm Wide)
AGS705/SUR	Surface Housing to suit AEM/SHEAR-30 Shear Magnet
AMS41SFM	Magnetic Solutions Compact Mortice Shear Magnet 12/24V DC Monitored (Separate PCB)
AMS41SSM	Magnetic Solutions Compact Surface Shear Magnet 12/24V DC Monitored (Separate PCB)
AMS41GF-KIT	Magnetic Solutions Glass Bracket for AMS41SSM
AMSGFAD	Magnetic Solutions Adhesive for Glass Door Bracket



Electromagnetic shear locks for fire doors.

The Deedlock AEMSF300 concealed electromagnetic Shear Lock has been tested to EN 1634-1 for 30 and 60 minute fire doors. When specifying or replacing your electromagnetic shear locks always ensure the product conforms to standards.

Install Deedlock electromagnets with the confidence that you are covered for both security and fire.

Available from all leading electrical and architectural wholesalers.



Securefast

Providing life safety and security solutions

www.securefast.co.uk

Sales Hotline: 01704 502801