

Product Data Sheet

GW62061H

IEC 309 HP range




IEC 309 HP: range of plugs and socket-outlets complying with the safety requisites defined by the international Standards IEC 60309-1 and IEC 60309-2 and assimilated at European level as EN 60309-1 and EN 60309-2. This range expands GEWISS's assortment from 16A to 125A straight plugs, straight connectors and 10° flush-mounting socket-outlets with IP44/IP54 and IP66/IP67/IP68/IP69 degrees of protection to ensure full protection for all applications. The technopolymers and thickness used for the parts made of insulating material guarantee an elevated degree of mechanical and chemical agent resistance. All the sleeves and pins of the IEC 309 HP socket-outlets and plugs are surface-treated with nickel-plating to ensure full protection against corrosion, oxidation and abrasion. All the external metallic elements of the IEC 309 HP plugs and socket-outlets are made of stainless steel (the threaded metallic inserts for the body-grip coupling of the 63-125A versions are made of brass).

Colour	Red	Rated current (A)	125		
IP degree	IP66/IP67/IP68/IP69	No. of poles	3P+N+E		
Shock resistance	IK09	Reference h	6		
Туре	Straight connector	Rated voltage	346 - 415 V		
Frequency	50/60 Hz	Terminal tightening capacity	16-50mm² flexible cables - 25-70mm² rigid cables		
Cable clamp tightening capacity	29.9 - 49 mm	Operating temperature	-25 +55 °C		
Type of wiring	Mantle terminal	Type of material	Halogen-free in compliance with EN 60754-2		
Electrocod	2211	Glow wire test	850 °C (active parts) - 650 °C (passive parts)		
Total number of operations	> 500	Breaking capacity at 1.1 Un	156 A		
Insulation resistance	> 10 MΩ	Thermo-pressure with ball	125 °C (active parts) - 80 °C (passive parts)		

	BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS												
Saline solution	Acids		Bases		Solvents			Mineral	UV				
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Alcohol	oil	rays			
Resistant	Not resistant	L <mark>imite</mark> d resistance	L <mark>imited</mark> resistance	Resistant	Resistant	Resistant	Resistant	Resistente	Resistant	Resistant			

DIMENSIONAL



TECHNICAL SYMBOLOGY











Mantle terminal

Halogen-free in compliance with EN

- 650 °C (passive parts)

850 °C (active parts) 125 °C (active parts) - 80 °C (passive

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com sat@gewiss.com Last update 03/04/2019 Data, measures, designs and pictures are shown only as informativ purposes, and could be changed without previous notice