



SEL212

### Safety Lampholders

#### Characteristics:

- Complies with BS EN 7895.
- T2 heat resistance rating: 210°C.
- Automatically disconnect power at the contacts when the lamp is removed.
- 50.8mm fixing centres for non-access versions. Use with mounting blocks **MB326E/MT**.
- Body angle of angled battens set at 30°.
- Access lampholders have integral **RL624** ceiling rose base and heat resisting PVC tails.

Description	Pack qty.	Cat ref.
<b>Safety Bayonet Cap Cord Grip Lampholders</b>		
Cord Grip Lampholders - Short Skirt	20	<b>SEL212</b>



SEL354

#### Safety Straight Batten Lampholders

Three Terminal - Home Office Shield	20	<b>SEL354</b>
-------------------------------------	----	---------------

#### Safety Access Batten Lampholders

Straight 2 Terminal Body, 3 Terminal and Earth Base - Home Office Shield	10	<b>SEL96T</b>
Angled 2 Terminal Body, 3 Terminal and Earth Base - Home Office Shield	10	<b>SEL106T</b>

#### Safety Access Batten Lampholder with Safety Cover

Batten Lampholder with Safety Cover	10	<b>SEL96TSC</b>
-------------------------------------	----	-----------------



SEL96T



624SEL212/6

### Safety Pendants Sets with Access Ceiling Rose

#### Characteristics:

- Pendant set complies with BS EN 60598-1.
- Capacity of each terminal: 3 x 1.00mm<sup>2</sup> conductor.
- Barriers between terminals.
- Flexible pendant cord restraining hooks.
- Fixing centres 50.8mm.
- Feet on base to aid mounting on uneven surfaces.
- Three separate knockouts accept 1, 2 or 3 x 1.5mm<sup>2</sup> conductors.
- Optional halo **RL602**.

Description	Pack qty.	Cat ref.
<b>Safety Pendants Sets with Access Ceiling Rose</b>		
Pendant Set 6" - Short Skirt	10	<b>624SEL212/6</b>
Pendant Set 9" - Short Skirt	10	<b>624SEL212/9</b>
Pendant Set 12" - Short Skirt	10	<b>624SEL212/12</b>
<b>Pendant Set with Access Ceiling Rose with Safety Cover</b>		
Pendant Set 6" with Safety Cover	10	<b>624SEL212SC6</b>