



CDC225U



CFC425U

### 2 & 4 Pole RCCBs

#### Characteristics

- To open a circuit automatically in the event an earth fault between line and earth, and/or neutral and earth.

#### Technical Data

- Conforms to BS EN 61008, IEC1008

- Terminal capacities: 16-63A Rigid 25mm<sup>2</sup>, Flexible 16mm<sup>2</sup> / 80 & 100A Rigid 50mm<sup>2</sup>, Flexible 35mm<sup>2</sup>

#### Features

- Positive contact indication is provided by the rectangular flag indicator

- Red = Closed

- Green = Open

- Indication of trip is provided by the flag indicator

- Yellow = Tripped


- All RCCBs have trip free mechanisms and can be padlocked either on or off with the use of a **MZN175**.

#### Operating Voltage

- 2P 127- 230V A.C.

- 4P 230 - 400V A.C.

Sensitivity type A	2 Pole Type F Cat ref.	4 Pole Type F Cat ref.	2 Pole Type B Cat ref.	4 Pole Type B Cat ref.	2 Pole Type A Cat ref.	4 Pole Type A Cat ref.
<b>RCCBs Sensitivity 30mA</b>						
RCCB 25A 30mA	<b>CDF525U</b> *	<b>CDF625U</b> *	<b>CDB525E</b> *	-	<b>CDA225U</b>	<b>CDA425U</b>
RCCB 40A 30mA	<b>CDF540U</b> *	<b>CDF640U</b> *	<b>CDB540E</b> *	<b>CDB640E</b> *	<b>CDA240U</b>	<b>CDA440U</b>
RCCB 63A 30mA	<b>CDF563U</b> *	<b>CDF663U</b> *	-	<b>CDB663E</b> *	<b>CDA263U</b>	<b>CDA463U</b>
RCCB 80A 30mA	-	-	-	-	<b>CDA580U</b> *	<b>CDA680U</b> *
RCCB 100A 30mA	-	-	-	-	<b>CDA584U</b> *	<b>CDA684U</b> *
RCCB 125A 30mA	-	-	-	-	-	<b>CDA690</b> *
<b>RCCBs Sensitivity 100mA</b>						
RCCB 25A 100mA	-	-	-	-	<b>CEA225U</b>	-
RCCB 40A 100mA	-	-	-	-	<b>CEA240U</b>	<b>CE440J</b>
RCCB 63A 100mA	-	-	-	-	<b>CEA263U</b>	<b>CE463J</b>
RCCB 80A 100mA	-	-	-	-	<b>CEA580U</b> *	<b>CEA680U</b> *
RCCB 100A 100mA	-	-	-	-	<b>CEA584U</b> *	<b>CEA684U</b> *
<b>RCCBs Sensitivity 300mA</b>						
RCCB 25A 300mA	-	-	-	-	<b>CFA225U</b>	<b>CF425J</b>
RCCB 40A 300mA	-	-	-	-	<b>CFA240U</b>	<b>CF440J</b>
RCCB 63A 300mA	-	-	-	-	<b>CFA263U</b>	<b>CF463J</b>
RCCB 80A 300mA	-	-	-	-	-	<b>CFA680U</b> *
RCCB 100A 300mA	-	-	-	-	<b>CFA584U</b> *	<b>CFA684U</b> *
RCCB 125A 300mA	-	-	-	-	-	<b>CFA690</b> *
<b>RCCBs Time Delayed</b>						
RCCB 100A 100mA	-	-	-	-	<b>CNA584U</b> *	<b>CNA684U</b> *
RCCB 100A 300mA	-	-	-	-	<b>CPA584U</b> *	<b>CPA684U</b> *



CZN006

### Terminal Covers

Current Rating	2 Pole Cat ref.	4 Pole Cat ref.
16 - 63A	<b>CZN005</b>	<b>CZN006</b>
80 - 100A	<b>CZ007</b>	<b>CZ008</b>