



CEA684U

## RCCB 3P+N 100A 100mA A

### Technical characteristics

#### Architecture

Neutral position	right
Number of poles	4 P
Type of pole	3P+N
Fixing mode	DIN rail type O (symmetrical)

#### Main electrical features

Rated operational voltage $U_e$	230 / 400 V
Frequency	50/60 Hz
Rated current	100 A
Type of supply voltage	AC

#### Voltage

Rated insulation voltage	500 V
Max operating voltage	440 V
Rated impulse withstand voltage	4000 V

#### Electric current

Rated residual operating current	100 mA
Rated conditional short-circuit current $I_{nc}$ according to EN 61008-1	10 kA

#### Electric current / temperature

Rating current 30°C	100 A
---------------------	-------

#### Dimensions

Depth of installed product	70 mm
Height of installed product	85 mm
Width of installed product	72 mm

#### Power

Total power loss under $I_N$	21,48 W
------------------------------	---------

#### Tripping

Short-time delayed tripping	No
-----------------------------	----

#### Endurance

Electric endurance in number of cycles	10000
Number of mechanical operations	20000

#### Capacity

Number of modules	4
-------------------	---

#### Equipment

Quick connect	no
Can be accessorized	Yes

#### Standards

Standard text	EN 61008-1
---------------	------------

European directive WEEE	concerned
<b>Safety</b>	
Protection index IP	IP20
Residual current type	A
<b>Use conditions</b>	
Operating temperature	-25...60 °C