

Getting Technical



CMA30035 13A 1 Gang Zigbee Smart Switched Socket Outlet

With the smart socket you can plug in home appliances like lamps, TV, heaters, fans etc.

Simply turn them on and off manually, with your voice, smart device with the Click Smart+ App or with an automation, timer or schedule.



| Product Information | |
|--|------------------|
| Load Rating (A) | 13 |
| Voltage (V~) & Frequency (Hz) | 240 & 50 |
| Standby Current (mA) | 4 |
| Protocol | Zigbee |
| Open Air Wireless Range (M) | <160 |
| Signal Frequency | 2.4GHz |
| Terminal Size (mm) | 5.7 x 4.8 |
| Terminal Capacity - Solid (mm ²) | 3 x 2.5 or 2 x 4 |
| Single Pole Switched | Yes |
| Operational Temperature (°C) | -5 to +40 |
| Ingress Protection | IP20 |
| Indicator Colour | White & Orange |
| Product Standards | |
| BS 1363-2, BS EN 61000-6-1, BS EN 61000-6-3, BS EN 60669-2-1 in conjunction with BS EN 60669-1 | |



CMA30036 13A 2 Gang Zigbee Smart Switched Socket Outlet

With the smart socket you can plug in home appliances like lamps, TV, heaters, fans etc.

Simply turn them on or off manually with your voice, smart device with the Click Smart+ App or with an automation, timer or schedule.



| Product Information | |
|--|------------------|
| Load Rating (A) | 13 |
| Voltage (V~) & Frequency (Hz) | 250 & 50 |
| Standby Current (mA) | 4 |
| Protocol | Zigbee |
| Open Air Wireless Range (M) | <160 |
| Signal Frequency | 2.4GHz |
| Terminal Size (mm) | 5.7 x 4.8 |
| Terminal Capacity - Solid (mm ²) | 3 x 2.5 or 2 x 4 |
| Single Pole Switched | Yes |
| Operational Temperature (°C) | -5 to +40 |
| Ingress Protection | IP20 |
| Indicator Colour | White & Orange |
| Product Standards | |
| BS 1363-2, BS EN 61000-6-1, BS EN 61000-6-3, BS EN 60669-2-1 in conjunction with BS EN 60669-1 | |

Click Smart+ app
for ios & android



CSP010 Smart Gateway Hub

The Smart Hub is the control centre of all Zigbee Protocol devices within a smart home.

Even if the homes WIFI is unstable or interrupted smart devices will still be able to function normally.



| Product Information | |
|---|----------------------------|
| Rated Voltage (DC) | 1.8 - 3.3 |
| Operational Temperature (°C) | -10 to +55 |
| Working Humidity | 10%-90%RH (Non-condensing) |
| Protocol | Zigbee |
| Wireless Technology | WIFI 801.11 b/g/n |
| Signal Frequency | 400MHz |
| Ingress Protection | IP20 |
| Indicator Colour | Green |
| Product Dimensions (mm) | 90 (L) x 90 (W) x 23 (D) |
| Product Warranty (Years) | 1 |
| Product Standards | |
| BS EN 60950-1, BS EN 55035, BS EN 61000-3-2, BS EN 61000-3-3, BS EN 62311 | |

| Product Information | |
|--|------------------|
| Load Rating (A) | 13 |
| Voltage (V~) & Frequency (Hz) | 240 & 50 |
| Standby Current (mA) | 1 |
| Protocol | Zigbee |
| Open Air Wireless Range (M) | <160 |
| Signal Frequency | 2.4GHz |
| Fuse Fitted Rating & Type | 13A (BS 1362) |
| Terminal Capacity - Solid (mm ²) | 3 x 2.5 or 2 x 4 |
| Single Pole Switched | Yes |
| Operational Temperature (°C) | -5 to +40 |
| Ingress Protection | IP20 |
| Indicator Colour | White & Orange |
| Product Standards | |
| BS 1363-2, BS EN 61000-6-1, BS EN 61000-6-3, BS EN 60669-2-1 in conjunction with BS EN 60669-1 | |



CMA30651 13A Zigbee Smart Switched Fused Connection Unit

With the smart FCU you can control home appliances like kitchen appliances, towel rails, heaters etc.

Simply turn them on or off manually with your voice, smart device with the Click Smart+ App or with an automation, timer or schedule.

Even if the homes WIFI is unstable or interrupted smart devices will still be able to function normally.

