

### Description

Spryte™ LED downlight range is the ideal energy efficient non-fire rated solution for new build or retrofit halogen installations. Fitted with the edge-to-edge, multifaceted, 60° wide beam EnFiniti™ lens, these downlights allow for high light output and low glare while still providing a sparkling halogen like optical appearance in a compact sized fitting. Also available in 8W gimbal adjustable version alongside the fixed for maximum application flexibility.

**8 - 10W up to 1050 Lumens**  
**L70 25,000 Hours**



#### EN-DDL1019

10W Fixed Integrated IP44  
 Dimmable LED Downlight

### Features & Benefits

- Energy efficient LED downlight for new build or halogen and reflector lamp retrofit applications
- EnFiniti™ edge-to-edge multifaceted polycarbonate lens creates low glare and halogen like appearance
- Compact integrated driver for easy installation and low ceiling voids
- 8W supplied with fixed white bezel. 10W supplied with interchangeable round & square white bezels
- Available as non-dimmable and triac dimmable
- Pre-wired with 500mm 2 core cable
- Fixed & adjustable versions IP44 rated
- 1.5kV surge protection
- **3 year warranty**


EN-DDL1019  
 SUPPLIED WITH  
 INTERCHANGEABLE  
 SQUARE & ROUND BEZELS



Cat. No.	Watts	Beam	Colour	Lumens	lm/W	L70 Life (hrs)	Overall [Ø]	Cutout [Ø]	Recess	Subst.
<b>NON-DIMMABLE FIXED</b>										
EN-DL10160/30	8W	60°	3000K	620lm	78	25,000	78mm	60mm	60mm	50W
EN-DL10160/40	8W	60°	4000K	680lm	85	25,000	78mm	60mm	60mm	50W
<b>TRIAC DIMMABLE FIXED</b>										
EN-DDL10160/30	8W	60°	3000K	620lm	78	25,000	78mm	60mm	60mm	50W
EN-DDL10160/40	8W	60°	4000K	680lm	85	25,000	78mm	60mm	60mm	50W
<b>TRIAC DIMMABLE ADJUSTABLE</b>										
EN-DDL10260/30	8W	60°	3000K	620lm	78	25,000	90mm	70mm	60mm	50W
EN-DDL10260/40	8W	60°	4000K	680lm	85	25,000	90mm	70mm	60mm	50W
<b>TRIAC DIMMABLE HIGH OUTPUT FIXED</b>										
EN-DDL1019/30	10W	60°	3000K	1000lm	100	25,000	105mm	90mm	65mm	100W
EN-DDL1019/40	10W	60°	4000K	1050lm	105	25,000	105mm	90mm	65mm	100W

Matt white finish only

### Technical Information



(RD) Recess Depth (see table)  
 (OD) Overall [Ø] (see table)



**EN-DDL10160**  
8W Fixed Integrated IP44  
Dimmable LED Downlight

**EN-DDL10260**  
8W Adjustable Integrated IP44  
Dimmable LED Downlight

20° gimbal  
adjustment

Downlights

Pre-wired with  
500mm 2 Core flex Cable

**EN-DDL1019**

**EN-DDL10160**

**EN-DDL10260**

Only 60mm recess depth

Only 60mm recess depth

Only 65mm recess depth

60mm Cutout [Ø]  
Halogen Retrofit

70mm Cutout [Ø]  
Halogen Retrofit

90mm Cutout [Ø]