

Product Description:

The Helius™ range of floodlights are perfect for both residential and commercial IP65 applications. Their slim profile and clean black finish make them as unobtrusive as possible. Available in 10W, 30W, 50W, 100W, 200W and 300W versions with black housing.

Product Image:




Product Features:


- IP65 rated LED floodlight rated with slim design
- Durable high quality paint minimises impact of corrosion
- Tempered glass provides excellent protection
- Die-cast aluminium housing
- Pre-wired with 800mm of cable
- 1.5kV surge protection
- Warning Note: Not suitable for post top mounting
- 3 year warranty

10W Adjustable IP65 LED Floodlight

Line Drawing Image



Polar Curve Image



Product Specs:

Technology	LED	Number of LEDs	1
Luminaire Distribution	Direct	Lifetime L70 (hrs)	25000
Input Voltage	220~240V AC	Input Frequency	50/60HZ
Dimmable	No	IP Rating	IP65
IK Rating	IK08	Power Factor	0.9
Lamp Base	None	Height (mm)	135
Width (mm)	115	Surge Protection (kV)	1.5

SKU Table and Ordering

SKU Code	Wattage	Lumens	Lumens/Watt	Colour	Beam Angle	Ra	SDCM
EN-FL10A/40	10	750	75	4000	120	70	6

Compliance & Approvals:



Warranty

This product has a warranty period of 3 Years.

Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Enlite Sales & Distribution
Apex Park
6 Little Burrow
Welwyn Garden City AL7 4SW
United Kingdom
Tel : +44 (0) 1707 35 18 20