

Product Description:

Product Image:



115mm Diameter Firehood

Product Features:

- UK Patent GB2424693
- International PCT / GB03/003229
- Fully breathable fire hood for low/mains downlights allows heat
- from the lamp to be effectively dissipated preventing the terminal
- block and fitting from overheating
- An intumescent material envelope expands to fill the hood and seal the downlight cut-out in the ceiling in the event of a fire in the room below
- Suitable for 30 and 60 minute fire rated ceilings
- Unique self supporting and adjustable fixing method allows for installation in ceilings up to 35mm thick
- Failure to perform insurance - £10M cover (subject to correct installation)
- Tested to BS476 Part 21
- In addition, Aurora firehoods are tested to BS EN ISO 140-3:1995
- & BS EN ISO 140-6:1998 (Acoustics), confirming that they maintain the ability for an internal or separating floor to provide sound insulation

Product Specs:

Fire Protection	Yes	Length (mm)	200
Width (mm)	200	Weight (Kg)	0.25

SKU Table and Ordering:

SKU Code	Finish Colour
AU-FH200	White
AU-FH200BK	Black

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.