

**Product Description:**

Introducing the stylish CurveE™ LED downlight range, this low glare downlight has a sleek baffled design with the light source recessed back to reduce glare. Available in matt white these triac dimmable downlights are an ideal non-fire rated solution for hospitality and residential applications in areas where fire rating is not required.


**Product Image:**



**Product Features:**

10W Baffled Dimmable IP44 LED Downlight

**Line Drawing Image**



**Product Specs:**

Technology	LED	Luminaire Distribution	Direct
Lifetime L70 (hrs)	25000	Input Voltage	220~240V AC
Dimmable	Yes	Dali	No
IP Rating	IP44	Operating Temp. (Max) °C	45
Power Factor	0.90	Overall Diameter (mm)	85
Recess Depth (mm)	87	Cutout Diameter (mm)	70
Lamp Base	None	Height (mm)	72
Surge Protection (kV)	2.0		

## SKU Table and Ordering

SKU Code	Wattage	Lumens	Lumens/Watt	Colour	Beam Angle	Ra	SDCM
EN-DLB102D/30	10	820	82	3000	60	80	6
EN-DLB102D/40	10	880	88	4000	60	80	6

## Compliance & Approvals:



## Warranty

This product has a warranty period of 3 Years.

Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

**UK Enlite Sales & Distribution**  
Apex Park  
6 Little Burrow  
Welwyn Garden City AL7 4SW  
United Kingdom  
Tel : +44 (0) 1707 35 18 20