

Description

The Helius™ range of floodlights are perfect for both residential and commercial IP65 applications. Their slim profile and clean black finish make them as unobtrusive as possible. Available in 10W, 30W, 50W, 100W, 200W and 300W versions with black housing.

Features & Benefits

- IP65 rated LED floodlight rated with slim design
- Durable high quality paint minimises impact of corrosion
- Tempered glass provides excellent protection
- Die-cast aluminium housing
- Pre-wired with 800mm of cable
- 1.5kV surge protection
- Warning Note: Not suitable for post top mounting
- **3 year warranty***

10 - 300W

up to **22,500 Lumens**

L70 25,000 Hours



EN-FL10A
10W Adjustable
IP65 LED Floodlight



EN-FL30A
30W Adjustable
IP65 LED Floodlight




EN-FL50A
50W Adjustable
IP65 LED Floodlight

Cat. No.	Watts	Colour	Lumens	L70 Life (hrs)	H x W x D (mm)	BL x BW (mm)	Halogen Subst.
EN-FL10A/40	10W	4000K	750lm	25,000	135 x 115 x 40mm	85 x 102mm	60W
EN-FL30A/40	30W	4000K	2250lm	25,000	230 x 195 x 60mm	150 x 180mm	100W
EN-FL50A/40	50W	4000K	3750lm	25,000	285 x 240 x 70mm	188 x 212mm	150W
EN-FL100A/40	100W	4000K	7500lm	25,000	315 x 335 x 100mm	155 x 310mm	200W
EN-FL100A/65	100W	6500K	7500lm	25,000	315 x 335 x 100mm	155 x 310mm	200W
EN-FL200A/40	200W	4000K	14000lm	25,000	380 x 380 x 120mm	220 x 350mm	750W
EN-FL200A/65	200W	6500K	14000lm	25,000	380 x 380 x 120mm	220 x 350mm	750W
EN-FL300A/40	300W	4000K	22500lm	25,000	455 x 455 x 125mm	300 x 410mm	1500W
EN-FL300A/65	300W	6500K	22500lm	25,000	455 x 455 x 125mm	300 x 410mm	1500W

*Warranty covers LED chip & driver

Technical Information



- (H) Height (see table)
- (W) Width (see table)
- (D) Depth (see table)
- (BL) Bracket Length (see table)
- (BW) Bracket Width (see table)



EN-FL100A
100W Adjustable
IP65 LED Floodlight



EN-FL200A
200W Adjustable
IP65 LED Floodlight



EN-FL300A
300W Adjustable
IP65 LED Floodlight

COB LED CHIPS