

Accessories

| metric locknuts | | | | | PG locknuts | | NPT locknuts | | stop plug | |
|---|-------------------------------|--------------------------|-----------------------------|-------------------|--|-------------------|-----------------------|-------------------|--------------------|-----------------|
| nickel plated brass, plated steel, stainless steel, nylon black or grey | | | | | nickel plated brass, Zinc, nylon black or grey | | Zinc or nylon (black) | | nylon metric black | nylon PG (grey) |
| | | | | | | | | | | |
| nickel plated brass part number | nickel plated EMC part number | plated steel part number | stainless steel part number | nylon part number | nickel plated brass part number | nylon part number | zinc part number | nylon part number | metric part number | PG part number |
| B-M12 | | | | LM12-N# | B-PG7 | PG7-N# | | | SP-M12* | SP-PG7* |
| B-M16 | | S-M16 | SS-M16 | LM16-N# | B-PG9 | PG9-N# | | | SP-M16 | SP-PG9 |
| B-M20 | B-M20-EMC | S-M20 | SS-M20 | LM20-N# | B-PG11 | PG11-N# | Z-050 | 050-NB | SP-M20 | SP-PG11 |
| B-M25 | B-M25-EMC | S-M25 | SS-M25 | LM25-N# | B-PG13 | PG13-N# | Z-075 | 075-NB | SP-M25 | SP-PG13 |
| B-M32 | B-M32-EMC | S-M32 | SS-M32 | LM32-N# | B-PG16 | PG16-N# | Z-100 | 100-NB | SP-M32 | SP-PG16 |
| B-M40 | B-M40-EMC | S-M40 | SS-M40 | LM40-N# | B-PG21 | PG21-N# | Z-125 | | SP-M40* | SP-PG21 |
| B-M50 | | S-M50 | SS-M50 | LM50-N# | B-PG29 | PG29-N# | Z-150 | | | SP-PG29 |
| B-M63 | | S-M63 | SS-M63* | LM63-N# | B-PG36 | PG36-N# | Z-200 | | | |
| B-M75 | | | | | B-PG42 | PG42-N# | | | | |
| | | | | | B-PG48 | PG48-N# | | | | |

add B or G to specify colour. eg. LM20-NB for Black

sealing washers

Polyester Elastomer, Neoprene and fibre face sealing washers

| Polyester Elastomer Metric | Neoprene Metric | Neoprene PG | Fibre Metric | Fibre PG | |
|----------------------------|---------------------------|-----------------------|------------------------|---------------------------|--------|
| | | | | | |
| metric thread part number | metric thread part number | PG thread part number | NPT thread part number | metric thread part number | |
| | SW12 | SWPG7 | FW12 | FWPG7 | |
| RSW16 | SW16 | SWPG9 | FW16 | FWPG9 | |
| RSW20 | SW20 | SWPG11 | SW050 | FW20 | FWPG11 |
| RSW25 | SW25 | SWPG13 | SW075 | FW25 | FWPG13 |
| RSW32 | SW32 | SWPG16 | SW100 | FW32 | FWPG16 |
| RSW40 | SW40 | SWPG21 | SW125 | FW40 | FWPG21 |
| RSW50 | SW50 | SWPG29 | SW150 | FW50 | FWPG29 |
| RSW63 | SW63 | SWPG36 | SW200 | FW63 | FWPG36 |
| | | SWPG42 | | | |
| | | SWPG48 | | | FWPG48 |

earthing washers

| shake proof washer | earth tag washer |
|---------------------------|---------------------------|
| | |
| metric thread part number | metric thread part number |
| SPW16 | |
| SPW20 | ET-M20 |
| SPW25 | ET-M25 |
| SPW32 | |
| | |
| | |
| | |

fixing clips

plated steel with black pvc liner or stainless steel.
LFH liner available on request



to fit conduit size

part number

part number

conduit clip

nylon conduit clip with integral lid - black or grey

(For fixing rails & accessories contact Flexicon)



to fit nominal conduit sizes

conduit clip for corrugated

conduit clip for plain or rigid



fclamp

EC

end cap

Nylon PA66 end cap to snap over end of conduit and provide a smooth entry bush to prevent snagging and sharp edges, and provide a neat finish when no connectors are used.



end cap

REC

rubber end cap

Thermoplastic elastomer cap used to seal end of conduit. Can be cut to size depending on size of cable. Can be additionally secured using cable tie (not supplied).



part number

to fit conduit size

outlet ID mm

| | | | | | | | | | | |
|-----|--------|-----------|----|-------|----------|--------------|-------|-------|-----|------|
| 10 | FCC10 | FCC10-SS* | 10 | FCL10 | | | REC10 | 10 | 0-7 | |
| 12 | FCC12 | FCC12-SS | 13 | FCL13 | | | REC13 | 13 | 0-7 | |
| 16 | FCC16 | FCC16-SS | 16 | FCL16 | FCL16B-P | FCLAMP- 3-16 | EC16B | REC16 | 16 | 0-11 |
| 20 | FCC20 | FCC20-SS | 18 | FCL18 | FCL18B-P | | | | | |
| 25 | FCC25 | FCC25-SS | 20 | FCL20 | FCL20B-P | | | | | |
| 32 | FCC32 | FCC32-SS | 21 | FCL21 | FCL21B-P | FCLAMP- 3-21 | EC21B | REC21 | 21 | 0-15 |
| 40 | FCC40 | FCC40-SS | 25 | FCL25 | FCL25B-P | | | | | |
| 50 | FCC50 | FCC50-SS | 28 | FCL28 | | FCLAMP- 4-28 | EC28B | REC28 | 28 | 0-21 |
| 63 | FCC63 | FCC63-SS* | 32 | FCL32 | | | | | | |
| 75 | FCC75 | | 34 | FCL34 | FCL33B-P | FCLAMP- 5-34 | EC34B | REC34 | 34 | 0-25 |
| 80 | FCC80 | | 42 | FCL42 | | FCLAMP- 6-42 | EC42B | REC42 | 42 | 0-34 |
| 106 | FCC106 | | 54 | FCL54 | | FCLAMP- 7-54 | EC54B | REC54 | 54 | 0-46 |
| | | | 67 | | | FCLAMP- 7-67 | | REC67 | 67 | 0-52 |
| | | | 80 | | | FCLAMP- 8-80 | | REC80 | 80 | 0-62 |

* indicates parts made to order on request and may be subject to MOQ and lead time

cable glands

Our range of Cable glands provides an easy to assemble, fast fit, liquid tight solution for multipurpose applications. Available in nickel plated brass they have been designed to provide the highest degree of functionality and safety.



| Thread Size. | Nickel plated brass | Thread Length (mm) | Cable Dia (min) (mm) | Cable Dia (max) (mm) | Spanner Size (mm) | Pack Quantity |
|--------------|---------------------|--------------------|----------------------|----------------------|-------------------|---------------|
| M16 | B-M16-CG | 12 | 4.5 | 10 | 20 | 10 |
| M20 | B-M20-CG | 12 | 7 | 13 | 24 | 10 |
| M25 | B-M25-CG | 12 | 9 | 17 | 29 | 10 |
| M32 | B-M32-CG | 15 | 11 | 21 | 36 | 2 |
| M40 | B-M40-CG | 15 | 19 | 28 | 45 | 2 |
| M50 | B-M50-CG | 15 | 27 | 35 | 54 | 1 |
| M63 | B-M63-CG | 15 | 35 | 47 | 67 | 1 |



| Thread Size. | EMC Nickel plated brass | Thread Length (mm) | Cable Dia (min) (mm) | Cable Dia (max) (mm) | Spanner Size (mm) | Pack Quantity |
|--------------|-------------------------|--------------------|----------------------|----------------------|-------------------|---------------|
| M16 | B-M16-CG-EMC | 12 | 4.5 | 9 | 20 | 10 |
| M20 | B-M20-CG-EMC | 12 | 7 | 12.5 | 24 | 10 |
| M25 | B-M25-CG-EMC | 12 | 9 | 16.5 | 29 | 10 |
| M32 | B-M32-CG-EMC | 15 | 11 | 21 | 36 | 2 |
| M40 | B-M40-CG-EMC | 15 | 19 | 28 | 45 | 2 |
| M50 | B-M50-CG-EMC | 15 | 27 | 35 | 54 | 1 |

Technical Details

- Material: Nickel plated brass
- IP Rating: IP68 (10 bar) + IP69
- Produced and tested in accordance with EN 50262:1999
- Temperature range: -40°C to +100°C (static) -20°C to +100°C (dynamic)
- UL Listed

Technical Details

- Material: EMC Nickel plated brass
- IP Rating: IP68 (10 bar)
- Produced and tested in accordance with EN 50262:1999
- Temperature range: -40°C to +100°C (static) -20°C to +100°C (dynamic)
- UL Listed