# Hamilton Technical Specification

# CATEGORY:

## **EUROFIX AV/AUDIO/HDMI SOCKETS**

Technical Insert Ref: Description:

MOD-HDMI	HDMI Chassis Mounted Socket Type A*	Current Rating: Contact Resista
MOD-USBAFF	(Female Mounted, Female Free) USB2 Panel Mounted Socket Type A*	Insulation Resista
	(Female Mounted, Female Free)	Dielectric Stren
MOD-USBAFM	USB2 Panel Mounted Socket Type A*	Life Cycle:
	(Female Mounted, Male Free)	Cable OD: Solder Compati
MOD-MP3 MOD-DIN9	3.5mm Stereo Socket (MP3) Screened* D-Range PC Socket 9 Pin*	Solder Compan
MOD-SVGA	D-Range SVGA Socket 15 Pin*	MOD-RCA1
		MOD-RCA2
Socket Type:	4mm Suitable for 'Banana' plugs	MOD-RCA3
MOD-BAN2	2 x Gold Binding Post Socket*	
	J. A A A A A A A A A A A A A A A A A A A	Current Rating:

### **EUROFIX AV/AUDIO/HDMI SOCKETS**

Technical Insert Ref: Description:

rrent Rating: ntact Resistar ulation Resist electric Streng e Cycle: ble OD: lder Compatib	tance: hth:	Mating connector dependent Mating connector dependent >1GW 500V DC 5000 4-9mm IEC 68-2-20
D-RCA1	1 x Gold	Phone/Audio Socket**
D-RCA2	2 x Gold	Phone/Audio Socket**
D-RCA3	3 x Gold	Composite Video/Audio**

Current Rating:	15 Amp
Voltage:	120VAC
Contact Resistance:	5mW Max

MOD-XLR

Latching Audio Connector 3 Pin XLR Socket\*

### **TECHNICAL SPECIFICATION:**

IP Rating:	IP2XD
Ambient Operating Temperature:	-5 to +40 C <sup>**</sup>
Location: Max Installation Altitude:	Internal Use Only 2000m
Module Dimensions:	25 x 50mm

**Note:** Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box a suitable barrier MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.

