

Item Image



Push On/Off 4 Gang 2 Way 250 max 40 min

Primary Range	Plastic Dimmer
Insert Type	
Plate Finish	White
Frame Finish	
Switch Colour	White
Body & Switch Trim	
Height	Double = 86mm
Width	Double = 146mm
Depth	
Fixing Hole Centres	
Minimum Wall Box Depth	35
Wattage	
Switched Poles	
Current Rating	
Voltage	
Max load	
Contact Gap Minimum	
Terminal Capacity 1	
Terminal Capacity 2	
Terminal Capacity 3	
Terminal Capacity 4	
Terminal Capacity 5	
Earth Terminal Capacity 1	
Earth Terminal Capacity 2	
Earth Terminal Capacity 3	
Earth Terminal Capacity 4	
Earth Terminal Capacity 5	
Product Class 1	
Ambient Operating Temperature	
Recommended Location	
Standard/Approval	BS EN 60669-2-1
Patents and Trademarks	

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at August 2012 E&OE

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK  
 T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com  
 www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary)  
 Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire  
 Registered in London No. 941624 • VAT Registration No. 222 6607 84



BS EN ISO 9001:2008  
 CERT. No. FM11238

