

Hamilton[®] Technical Specification

SWITCHED SOCKETS

CATEGORY:

SWITCHED SOCKETS

Technical Insert Ref: Description:

SS1	1 gang 13A Double Pole Switched Socket
SS2	2 gang 13A Double Pole Switched Socket

GRID-IT SWITCHED SOCKETS MODULES

Technical Insert Ref: Description:

GSS1	1 gang 13A Double Pole Switched Socket
GSS2	2 gang 13A Double Pole Switched Socket

TECHNICAL SPECIFICATION:

Current Rating:	13 Amp
Voltage:	220/250V AC
IP Rating:	IP2XD
Max Load:	13 Amp
Switched Poles:	Double
Contact Gap Minimum:	3mm
Product Class 1:	Must be earthed
GRID-IT Product Class 1:	Face plate must be earthed
Ambient Operating Temperature:	-5 to +40 C
Location:	Internal Use Only

Max Installation Altitude:	2000m
Dual Earth:	Yes

Standard Hamilton manufactured electrical accessories are designed to be mounted on BS4662:2006 flush wall boxes.

STANDARDS:

BS EN ISO Standard:	BS 1363-2 Inc. amendment 1,2,3
ASTA Licence No:	1046 (SS1 and SS2 only)

TERMINAL CAPACITY:

	2.5mm ²	4mm ²	6mm ² Multi-Strand	10mm ²
Terminal Capacity	4	3	2	1
Earth Terminal Capacity	4	3	2	1

Fixing Centres:


13A SWITCHED SOCKETS

60.3mm



SS1

120.6mm



SS2

Fixing Centres:


60.3mm grid to wall box
49.2mm plate to grid

120.6mm grid to wall box
106.5mm plate to grid

GRID-IT SWITCHED SOCKETS MODULES



GSS1



GSS2