

Hamilton[®] Technical Specification

UNSWITCHED SOCKETS

CATEGORY:

2A UNSWITCHED SOCKETS AND FLOOR SOCKETS

Current Rating: 2 Amp

Max Load: 2 Amp

Technical Insert Ref: Description:

US2 1 gang 2A Unswitched Socket

5A UNSWITCHED SOCKETS AND FLOOR SOCKETS

Current Rating: 5 Amp

Max Load: 5 Amp

Technical Insert Ref: Description:

US5 1 gang 5A Unswitched Socket

13A UNSWITCHED SOCKETS AND FLOOR SOCKETS

Current Rating: 13 Amp

Max Load: 13 Amp

Technical Insert Ref: Description:

US13 1 gang 13A Unswitched Socket

US99 2 gang 13A Unswitched Socket

EUROFIX 13A UK UNSWITCHED SOCKET MODULE

MOD-ENG13A 1 gang 13A UK Unswitched Socket

TECHNICAL SPECIFICATION:

Voltage: 220/250V AC
IP Rating: IP2XD
Switched Poles: None
Contact Gap Minimum: None
Product Class 1: Must be earthed
Ambient Operating Temperature: -5 to +40 C
Location: Internal Use Only
Max Installation Altitude: 2000m
Shuttered: Yes

Standard Hamilton manufactured electrical accessories are designed to be mounted on BS4662:2006 flush wall boxes.





STANDARDS:

BS EN ISO Standard:

2A and 5A Unswitched BS 546
 13A Unswitched BS 1363-2

TERMINAL CAPACITY:

	1mm ²	1.5mm ²	2.5mm ²	4mm ²	6mm ² Multi-strand	10mm ²
2A and 5A Terminal Capacity	5	4	2	1		
2A and 5A Earth Terminal Capacity	5	4	2	1		
13A Terminal Capacity			3	3	2	1
13A Earth Terminal Capacity			3	3	2	1

Fixing Centres:	2A & 5A UNSWITCHED SOCKETS	13A UNSWITCHED SOCKETS	EUROFIX 13A UNSWITCHED SOCKET MODULE
60.3mm	 <p>US2 US5</p> <p>US2 US5</p>	 <p>US13</p> <p>US13</p>	 <p>MOD-ENG13A</p>
120.6mm		 <p>US99</p> <p>US99</p>	