

Product Description:

The brand E6™ PRO is a revolution in LED downlight performance and installation. Utilising the unique RapidWire connection system, the whole product can be fully wired and installed in a matter of seconds. The use of latching terminals provides the security of screw terminations for both solid and stranded core cables and can be wired even faster than standard push fits. The removable connector allows full circuit insulation resistance testing without risking any damage to the downlight, which can be simply plugged in afterwards.

Product Features:


- Quick, easy and fully tool-free installation
- Plug in connection system for first fix and insulation resistance testing
- High performance up to 117lm/W
- EnFiniti™ edge-to-edge multifaceted polycarbonate lens for low glare and halogen like appearance
- Wide 60° beam angle delivers increased light distribution
- Fibre based insulation coverable - up to 300mm
- Super slim interchangeable IP65 bezels provide a high end sleek finish
- Compatible with Aurora FastRfix™ connector
- Tested in 30, 60 and 90-minute fire rated ceilings
- SEAI: EN-DE62PRO/30 - LIG84982
- SEAI: EN-DE62PRO/40 - LIG84983
- 5 year warranty

Product Image:



E6™ PRO Adjustable 6W Dimmable Fire Rated LED Downlight

Line Drawing Image



Product Specs:

Technology	LED	Number of LEDs	12
Luminaire Distribution	Direct	Lifetime L70 (hrs)	50000
Input Voltage	220~240V AC	Input Frequency	50/60HZ
Dimmable	Yes	IP Rating	IP20
Fire Protection	Yes	Acoustic Rated	Yes
Power Factor	0.8	Overall Diameter (mm)	95
Recess Depth (mm)	110	Cutout Diameter (mm)	80
Lamp Base	None	Height (mm)	105
Surge Protection (kV)	1.5		

SKU Table and Ordering

SKU Code	Wattage	Lumens	Lumens/Watt	Colour	Beam Angle	Ra
EN-DE62PROEMMW/30	6	680	113.33	3000	60	80
EN-DE62PROEMMW/40	6	700	116.67	4000	60	80
EN-DE62PROEMPC/30	6	680	113.33	3000	60	80
EN-DE62PROEMPC/40	6	700	116.67	4000	60	80
EN-DE62PROEMSN/30	6	680	113.33	3000	60	80
EN-DE62PROEMSN/40	6	700	116.67	4000	60	80
EN-DE62PROEMW/30	6	680	113.33	3000	60	80
EN-DE62PROEMW/40	6	700	116.67	4000	60	80
EN-DE62PROMW/30	6	680	113.33	3000	60	80
EN-DE62PROMW/40	6	700	116.67	4000	60	80
EN-DE62PROPC/30	6	680	113.33	3000	60	80
EN-DE62PROPC/40	6	700	116.67	4000	60	80
EN-DE62PROSN/30	6	680	113.33	3000	60	80
EN-DE62PROSN/40	6	700	116.67	4000	60	80
EN-DE62PROW/30	6	680	113.33	3000	60	80
EN-DE62PROW/40	6	700	116.67	4000	60	80

Compliance & Approvals:



Warranty

This product has a warranty period of 5 Years. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Enlite Sales & Distribution
Apex Park
6 Little Burrow
Welwyn Garden City AL7 4SW
United Kingdom
Tel : +44 (0) 1707 35 18 20