



5 Year Warranty

L70 50,000hrs

Triac dimmable as standard

Emergency option

White, Matt White, Polished  
Chrome & Satin Nickel  
bezel finish options



**EN-DE6PRO**  
(H) 100mm Height  
(OD) 85mm Overall (Ø)

**EN-DE62PRO**  
(H) 105mm Height  
(OD) 95mm Overall (Ø)

# E6<sup>TM</sup>PRO

LED fixed/adjustable fire rated downlights

make smart with



See pg.218-219 for compatibility table

Sparkling, low glare, multifaceted EnFiniti™ lens

Delivering up to 117lm/W

Slim, interchangeable IP65 bezels (fixed version) provide a sleek finish

IP20 bezel included for adjustable

SDCM <6 providing consistent light colour quality

Unique RapidWire connection system

Removable connector allows full circuit insulation resistance testing

Fibre based insulation coverable - up to 300mm

60° beam angle for maximum light distribution

Tested in 30, 60 and 90-minute fire rated ceilings



For Dimming Compatibility See pg.224-225



Fixed IP65

Adjustable



Cat. No. Watts Colour Lumens lm/W Beam Cutout [Ø]

**E6<sup>TM</sup>PRO Triac Dimmable Fixed (IP65 when used with IP65 Bezel)**

**EN-DE6PRO<sup>†</sup>/30** 6W 3000K 580lm 97 60° 70mm

**EN-DE6PRO<sup>†</sup>/40** 6W 4000K 620lm 103 60° 70mm

**E6<sup>TM</sup>PRO Triac Dimmable Adjustable**

**NEW EN-DE62PRO<sup>†</sup>\*/30** 6W 3000K 680lm 113 60° 80mm

**NEW EN-DE62PRO<sup>†</sup>\*/40** 6W 4000K 700lm 117 60° 80mm

**Accessories**

**EN-BZE8\*** E6<sup>TM</sup> PRO/E8<sup>TM</sup> Fixed IP65 Aluminium Downlight Bezel

\*Add suffix **W**, **MW**, **PC** or **SN** for White, Matt White, Polished Chrome or Satin Nickel finishes.

\*Add suffix **EM** for Emergency

