

technical hotline +44 (0)1268 563720

conduit and mini | cable management

Egatube Round Conduit

High Impact Conduit Heavy Gauge

High Impact Conduit Light Gauge

Heavy Gauge Coupling

Expansion Coupling

Inspection Coupling

3 METRE LENGTHS
BLK OR WHI

3 METRE LENGTHS
WHI ONLY

BLK OR WHI

BLK OR WHI

BLK OR WHI

Manufactured in accordance with BS 4607 and BS EN 50085, Parts 1 and 2.
STANDARD LENGTH: 3 metres.
MATERIAL: PVCu



16mm	HIP1	90m	HLG1WHI	90m	ESC1	50	EEC1BLK	25		
20mm	HIP2	90m	HLG2WHI	90m	ESC2	100	EEC2	100	EIS2	25
25mm	HIP3	90m	HLG3WHI	90m	ESC3	50	EEC3	50	EIS3	25
32mm	HIP4	30m	HLG4WHI	30m	ESC4	50	EEC4	10	*	
38mm	HIP5BLK	30m	HLG5WHI	30m	ESC5	25	EEC5	10	*	
50mm	HIP6BLK	30m	HLG6WHI	30m	ESC6	20	EEC6	10	*	

Wall thickness (nominal mm)
HIP1 1.7 HIP4 2.5
HIP2 1.8 HIP5 2.5
HIP3 1.9 HIP6 3.2

Wall thickness (nominal mm)
HLG1 1.1 HLG4 1.5
HLG2 1.2 HLG5 1.5
HLG3 1.5 HLG6 1.8

* For 32/38/50mm use square junction boxes (ERB page 369).

Spacer Bar Saddle

Spring Clip Saddle

Strap Saddle

Quickfit Spacer Saddle

Conduit Clip

LIGHT GAUGE COUPLINGS NOT REQUIRED
WHI ONLY


BLK OR WHI

BLK OR WHI

BLK OR WHI

BLK OR WHI

BLK OR WHI



LNB1WHI	25	ESB1	50		ES1	100		ECC1	50
LNB2WHI	100	ESB2	100	MEC2	100	ES2	100	ECC2	50
LNB3WHI	50	ESB3	100	MEC3	50	ES3	100	ECC3	50
LNB4WHI	50	ESB4	50	MEC4	25	ES4	50	ECC4	50
LNB5WHI	25	ESB5	25			ES5	50	ECC5WHI	50
LNB6WHI	25	ESB6	25			ES6	50		