

**Product Code:** CT300

**Description:** 250V~ 20A 4 Pole 1 In 3 Out Hub



### General Information

<b>Dimensions</b>	82mm (W) x 82mm (D) x 55mm (H)
<b>Material Composition</b>	Cover: Polycarbonate Base & Terminal Housing: Nylon (PA66) Terminals: Silver Plated Brass Terminal Screws: Steel and Yellow Passivated
<b>Maximum Voltage</b>	250V~ 50Hz
<b>Load Rating</b>	20A
<b>Rated Impulse Voltage</b>	4kV
<b>Ingress Protection</b>	IP20
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	10 Years

**Compatible Connectors** Input Connector: Compatible With 3 and 4 Pole Connectors (Complete or Female)  
Output Connectors: Compatible with 3 and 4 Pole Male Connectors

**Standards** BS 8488 : 2009+ A1 :2010  
EN 61535: 2009 + A1: 2013  
BS 5733: 2010 + A1: 2014



**Additional Information** Ensure that the mains supply is isolated before commencing installation. Pre-fabricating wiring systems manufactured to BS 8488 by other manufacturers may not be compatible or safely inter-connectable with this system. Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.