

Technical Specification

Product Code: MD018PW-DW

Description: 13A/10AX Double Pole Switch Module



General Information

Dimensions	25mm (W) x 53mm (H) x 20mm (D)
Aperture Dimensions	16mm (W) x 31.5mm (H)
Finish	Polar White
Materials	Rocker Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass
Maximum Voltage	250V 50Hz
Load Rating	13A/10AX (Suitable For Inductive Loads)
Terminal Size	3.5mmø
Terminal Torque	0.4Nm
Terminal Capacity	4 x 1.5mm ² or 2 x 2.5mm ²
Product Markings	Dish Washer
Back Box Depth	Dependent On Plate Used
Operational Temperature	-5°C to +40°C
Warranty	10 Years
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Suitable and matches the Definity, Mode, Polar & Part M ranges