

Technical Specification



Product Code: VPCH052WH Description: 13A Double Pole Switched Fused Connection Unit With Neon & Optional Flex





Representative Image

General Information

88mm (W) x 88mm (H) x 8mm (D) Dimensions **Dimensions With Gasket** 91mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Polished Chrome

Insert & Gasket Colour White

> Front Plate: Stainless Steel Materials

Insert, Switch, Fuse Drawer & Housing: Urea

Neon Lens: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

Load Rating 13A Plate Fixing Centres 60.3mm Terminal Size 5mmø **Terminal Torque** 2.5Nm

Terminal Capacity 4 x 2.5mm² or 2 x 4mm²

Switched Yes Double Pole Yes Twin Earth Terminals Yes **Neon Indicator** Yes (Red) Fuse Fitted 13A (BS 1362)

> Flex Outlet Yes (10mmø Through Front of the Plate)

Ingress Protection

Back Box Depth 25mm Minimum Operational Temperature -5°C to +40°C Warranty 10 Years

BS 1363-4: 2016 +A1: 2018 **Standards**

BS 1362:1973

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.