

**Technical Specification**

**Product Code:** GM2018PW-DW

**Description:** 20AX Double Pole Switch Module



**General Information**

<b>Dimensions</b>	24.5mm (W) x 50mm (H) x 22.5mm (D)
<b>Aperture Dimensions</b>	20mm (W) x 35mm (H)
<b>Module Frame Finish</b>	Polar White
<b>Switch Finish</b>	Polar White
<b>Laser Etched Legend</b>	Dishwasher
<b>Materials</b>	Body & Insert: Nylon Switch: Urea Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass
<b>Maximum Voltage</b>	250V 50Hz
<b>Load Rating</b>	20AX (Suitable For Inductive Loads)
<b>Terminal Size</b>	5mmø
<b>Termination Type</b>	Screw
<b>Terminal Torque</b>	1.2Nm
<b>Terminal Capacity</b>	3 x 2.5mm <sup>2</sup> or 1 x 4mm <sup>2</sup>
<b>Product Markings</b>	Dishwasher
<b>Back Box Depth</b>	Dependent On Plate Used
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	10 Years
<b>Standards</b>	BS EN 60669-1:2018

**Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.