


Technical Specification

Product Code: PRW156

Description: Non-Isolated Single Satellite Outlet



Representative Image

General Information

Dimensions	86mm (W) x 86mm (H) x 11mm (D)
Plate Design & Finish	Square Edge Polar White
Materials	Front Plate: Urea Earth Plate: Mild Steel Terminals: Brass
Plate Fixing Centres	60.3mm
Isolated	Non-isolated (Direct connection to aerial where 2 way signal is required)
Shielded	No
Ingress Protection	IP20
Back Box Depth	16mm Minimum
Operational Temperature	-5°C to +40°C
Warranty	20 Years

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Isolated socket will filter out any interference, if a 2 way signal is required, i.e. for use with satellite hard wire extensions, then a non-isolated outlet is required.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.
All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.