

# Technical Specification

Product Code: MD9125CH

Description: 10AX Intermediate Toggle Switch Module



## General Information

<b>Dimensions</b>	25mm (W) x 62mm (H) x 22mm (D)
<b>Finish</b>	Polished Chrome
<b>Materials</b>	Body: Nylon Terminals: Brass Terminal Screws: Brass Switch Front & Nut: Cast Zinc
<b>Maximum Voltage</b>	250V~ 50Hz
<b>Load Rating</b>	10AX (Suitable for Inductive Loads)
<b>Terminal Size</b>	4.9mm x 4.1mm
<b>Terminal Torque</b>	1.2Nm
<b>Terminal Capacity</b>	4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>
<b>Back Box Depth</b>	Dependent On Plate Used
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	10 Years
<b>Standards</b>	BS EN 60669-1:1999 +A1:2002 +A2:2008

## Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Suitable for Polished Chrome finish plates in Deco, Deco Plus, Define and Definity ranges.  
Polished Chrome