

Technical Specification

CLICK® ScolmoreGROUP

Product Code: DPSB752WH Description: 13A Ingot Double Pole Switched Fused Connection Unit With Neon





Representative Image

General Information

 $\begin{tabular}{lll} \textbf{Dimensions} & 88mm (W) \times 88mm (H) \times 8mm (D) \\ \begin{tabular}{lll} \textbf{Dimensions With Gasket} & 91mm (W) \times 91mm (H) \times 9mm (D) \\ \end{tabular}$

Plate Design & Finish Rounded Profile Satin Brass

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert & Housing: Urea

Switch & Fuse Drawer Cover: Stainless Steel

Neon Lens: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 13A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 2.5Nm

Terminal Capacity 4 x 2.5mm² or 2 x 4mm²

SwitchedYesDouble PoleYesTwin Earth TerminalsYes

Neon Indicator Yes (Red)
Fuse Fitted 13A (BS 1362)

Ingress Protection IP20

Back Box Depth 25mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 1363-4: 2016 +A1: 2018

BS 1362:1973

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.