

Technical Specification



Product Code: SIN425PWCH Description: 10AX Ingot 1 Gang Intermediate Plate Switch Insert





General Information

Dimensions 82.5mm (W) x 82.5mm (H) x 2.5mm (D)

Insert Finish Polar White Insert With Polished Chrome Switch

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black), PW (Polar

White) & RD (Red)

Materials Insert: Polycarbonate

Switch Cover: Stainless Steel Rear Housing: Nylon

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

 $\textbf{Maximum Voltage} \qquad 250 \text{V}{\sim}~50 \text{Hz}$

Load Rating 10AX (Suitable for Inductive Loads)

Plate Fixing Centres 60.3mm
Terminal Size 3.5mmø
Terminal Torque 0.5Nm

Terminal Capacity 4 x 1.5mm² or 2 x 2.5mm²

Intermediate Yes
Ingress Protection IP20

Back Box Depth 25mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range.



Technical Specification



Product Code: SIN425PWCH Description: 10AX Ingot 1 Gang Intermediate Plate Switch Insert

Compatible Cover Plates

Plate Dimensions 86mm (W) x 86mm (H) x 4mm (D)

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black), PW (Polar

White) & RD (Red)

Materials: Decorative: Stainless Steel, Black, Polar White & Red: Polycarbonate



SCP401BS




SCP401CH



SCP401SS



SCP401BK



SCP401PW

