

Technical Specification



Product Code: SIN536PWBS Description: 13A Ingot 2 Gang Double Pole Switched Socket Outlet Insert





Representative Image

General Information

Dimensions 142.5mm (W) x 82.5mm (H) x 2.5mm (D)

Insert Finish Polar White Insert With Brushed Stainless Switches

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black), PW (Polar

White) & RD (Red)

Materials Insert: Polycarbonate

Rear Housing: Urea

Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V~ 50Hz

Load Rating 13A
Plate Fixing Centres 120.6mm
Terminal Size 5mmø

Terminal Torque 2.5Nm

Terminal Capacity 4 x 2.5mm², 2 x 4mm²

Double Pole Yes
Twin Earth Terminals Yes
Ingress Protection IP20

Back Box Depth 35mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 1363-2: 2016 +A1: 2018

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Technical Specification



Product Code: SIN536PWBS Description: 13A Ingot 2 Gang Double Pole Switched Socket Outlet Insert


Compatible Cover Plates

Plate Dimensions 146mm (W) x 86mm (H) x 4mm (D)

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black), PW (Polar


White) & RD (Red)

Materials: Decorative: Stainless Steel, Black & Polar White: Polycarbonate






SCP436CH




SCP436SS

SCP436BS







SCP436BK SCP436PW SCP436RD