

## **Technical Specification**



Product Code: SIN536BKCH Description: 13A Ingot 2 Gang Double Pole Switched Socket Outlet Insert





Representative Image

## **General Information**

**Dimensions** 142.5mm (W) x 82.5mm (H) x 2.5mm (D)

Insert Finish Black Insert With Polished Chrome Switches

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black), PW (Polar

White) & RD (Red)

Materials Insert: Polycarbonate

Rear Housing: Urea

Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V~ 50Hz

Load Rating 13A
Plate Fixing Centres 120.6mm
Terminal Size 5mmø

**Terminal Torque** 2.5Nm

**Terminal Capacity** 4 x 2.5mm<sup>2</sup>, 2 x 4mm<sup>2</sup>

Double Pole Yes
Twin Earth Terminals Yes
Ingress Protection IP20

Back Box Depth 35mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS 1363-2: 2016 +A1: 2018

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



## **Technical Specification**



Product Code: SIN536BKCH Description: 13A Ingot 2 Gang Double Pole Switched Socket Outlet Insert


## **Compatible Cover Plates**

Plate Dimensions 146mm (W) x 86mm (H) x 4mm (D)


Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black), PW (Polar

White) & RD (Red)


Materials: Decorative: Stainless Steel, Black & Polar White: Polycarbonate









SCP436BS SCP436CH SCP436SS







SCP436BK SCP436PW SCP436RD