

Technical Specification

Product Code: FPBS504WH



Outlet





Representative Image

General Information

 $\begin{tabular}{lll} \textbf{Dimensions} & 146mm (W) x 88mm (H) x 1.3mm (D) \\ \begin{tabular}{lll} \textbf{Dimensions With Gasket} & 146mm (W) x 88mm (H) x 3mm (D) \\ \end{tabular}$

Plate Design & Finish Flat Plate Brushed Stainless

Insert Colour White

Materials Front Plate: Stainless Steel

Insert & Rear Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 45A

Plate Fixing Centres 120.6mm (Vertical Fixing)

 Terminal Size
 6mmø

 Terminal Torque
 2.5Nm

 Terminal Capacity
 1 x 16mm²

 Double Pole
 Yes

 Twin Earth Terminals
 Yes

Ingress Protection IP20
Back Box Depth 47mm

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 4177:1992

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.