

## **Technical Specification**



Product Code: SIN411BKBS Description: 10AX Ingot 1 Gang 2 Way Plate Switch Insert





## **General Information**

 $\textbf{Dimensions} \hspace{0.5cm} 82.5 \text{mm (W)} \times 82.5 \text{mm (H)} \times 2.5 \text{mm (D)}$ 

Insert Finish Black Insert With Brushed Stainless Switch

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black), PW (Polar

White) & RD (Red)

Materials Insert: Polycarbonate

Switch Cover: Stainless Steel Rear Housing: Nylon

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V~ 50Hz

Load Rating 10AX (Suitable for Inductive Loads)

Plate Fixing Centres 60.3mm
Terminal Size 3.5mmø
Terminal Torque 0.5Nm

**Terminal Capacity** 4 x 1.5mm<sup>2</sup> or 2 x 2.5mm<sup>2</sup>

Two Way Yes Ingress Protection IP20

Back Box Depth 25mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

**Additional Information** Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Interchangeable with modules in the MiniGrid Range.

UK Design Registration: 3015621



## **Technical Specification**



Product Code: SIN411BKBS Description: 10AX Ingot 1 Gang 2 Way Plate Switch Insert

## **Compatible Cover Plates**

Plate Dimensions 86mm (W) x 86mm (H) x 4mm (D)

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black), PW (Polar

White) & RD (Red)

Materials: Decorative: Stainless Steel, Black, Polar White & Red: Polycarbonate



SCP401BS



SCP401CH



SCP401SS



SCP401BK



SCP401PW

