

Technical Specification

CLICK® ScolmoregROUP

Product Code: VPBR038BK Description: 5A Round Pin Socket Outlet





General Information

Dimensions 88mm (W) x 88mm (H) x 8mm (D)

Dimensions With Gasket 91mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Polished Brass

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel

Insert: Urea

Rear Housing: Nylon Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V~ 50Hz

Load Rating 5A

Plate Fixing Centres 60.3mm

Terminal Size 5mmø
Terminal Torque 1.2Nm

Terminal Capacity 4 x 1.5mm² or 3 x 2.5mm²

Switched No
Twin Earth Terminals No
Ingress Protection IP20

Ingress Protection IP20

Back Box Depth 25mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 546: 1950

Additional Information Ensure that the mains supply is is:

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.