

Product Code: CL050

Description: 13A Fused Connection Unit With Optional Flex Outlet



General Information

Dimensions	80mm (W) x 80mm (H) x 42mm (D)
Finish	Metal Clad Grey
Materials	Front Plate & Pattress Box: Electrophoretically Coated Steel Insert, Fuse Drawer & Housing: Urea Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Load Rating	13A
Plate Fixing Centres	60.3mm
Terminal Size	5mmø
Terminal Torque	2.5Nm
Terminal Capacity	4 x 2.5mm ² or 2 x 4mm ²
Switched	No
Twin Earth Terminals	Yes
Fuse Fitted	13A (BS 1362)
Flex Outlet	Yes (10mmø Through Front of the Plate)
Back Box Depth	40mm Supplied
Earth Terminal Provided	Yes
Back Box Knockouts	5 x 20mm (2 on top, 1 on bottom, 1 on each side)
Operational Temperature	-5°C to +40°C
Warranty	10 Years
Standards	BS 1363-4: 2016 +A1: 2018 BS 1362:1973

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.