



# **Technical Specification**

### Product Code: SIN723PWCH

Description: 20A Ingot Double Pole Plate Switch With Neon Insert





**Representative Image** 

<b>General Information</b>	
Dimensions	82.5mm (W) x 82.5mm (H) x 2.5mm (D)
Insert Finish	Polar White Insert With Polished Chrome Switch
Cover Plate Finishes Available	BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar White)
Materials	Insert: Polycarbonate Rear Housing: Urea Switch Cover: Stainless Steel Neon Lens: Polycarbonate Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Load Rating	20A
Plate Fixing Centres	60.3mm
Terminal Size	5mmø
Terminal Torque	1.8Nm
Terminal Capacity	4 x 2.5mm <sup>2</sup>
Double Pole	Yes
Twin Earth Terminals	Yes
Neon Indicator	Yes (Red)
Ingress Protection	IP20
Back Box Depth	35mm Minimum
Operational Temperature	-5°C to +40°C
Warranty	10 Years
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Page 1 of 2 Rev.1.3 Errors & Omissions excluded. Specification is subject to change without notice.



## **Technical Specification**



Product Code: SIN723PWCH

**Description:** 20A Ingot Double Pole Plate Switch With Neon Insert

# Compatible Cover Plates Plate Dimensions 86mm (W) x 86mm (H) x 4mm (D) Cover Plate Finishes Available BS (Bruched Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar White) Materials: Decorative: Stainless Steel, Black & Polar White: Polycarbonate SCP423BS SCP423BC SCP423BS SCP423BC SCP423BS SCP423BC SCP423BK SCP423BK

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com

### Page 2 of 2 Rev.1.3 Errors & Omissions excluded. Specification is subject to change without notice.