


Technical Specification

Product Code: CMA205

Description: 45A 2 Gang Double Pole Switch With 13A Double Pole

Switched Socket Outlet & Neons





General Information

Dimensions 146mm (W) x 86mm (H) x 9.5mm (D)

Material Composition Front Plate & Rocker Switch: Urea

Rear Housing: Urea Neon Lens: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage250V~ 50HzFixing Centres120.6mmTerminal Size6mmøTerminal Torque2.5NmTerminal Capacity1 x 16mm²Pouble PoleYes

Double Pole Yes
Twin Earth Terminals Yes
Neon Indicator Yes

Back Box Depth 35mm Minimum

Temperature Rating -5°C to +40°C

Warranty 20 Years

Standards BS 4177: 1992

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

