

Technical Specification

CLICK® ScolmoreGROUP

Product Code: DPBR500BK Description: 45A Ingot 1 Gang Double Pole Plate Switch





Representative Image

General Information

 $\begin{array}{ccc} \textbf{Dimensions} & & 88\text{mm (W) x 88mm (H) x 8mm (D)} \\ \textbf{Dimensions With Gasket} & & 91\text{mm (W) x 91mm (H) x 9mm (D)} \\ \end{array}$

Plate Design & Finish Rounded Profile Polished Brass

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel

Insert & Rear Housing: Urea Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 45A

Plate Fixing Centres 60.3mm
Terminal Size 6mmø
Terminal Torque 2.5Nm
Terminal Capacity 1 x 16mm²
Double Pole Yes

Twin Earth Terminals
Ingress Protection
IP20

Back Box Depth 35mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.