


## Technical Specification

Product Code: DPSB535WH

Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet



Representative Image

### General Information

|                         |  |
|-------------------------|--|
| Dimensions              | 88mm (W) x 88mm (H) x 8mm (D)  |
| Dimensions With Gasket  | 91mm (W) x 91mm (H) x 9mm (D)  |
| Plate Design & Finish   | Rounded Profile Satin Brass  |
| Insert & Gasket Colour  | White  |
| Materials               | Front Plate: Stainless Steel<br>Insert & Housing: Urea<br>Switch Cover: Stainless Steel<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated<br>Contacts: Silver "on-lay" Copper / Brass<br>Internal Busbars: Formed Pressed Brass<br>Earth Strap: Mild Steel |
| Maximum Voltage         | 250V~ 50Hz   |
| Load Rating             | 13A  |
| Plate Fixing Centres    | 60.3mm   |
| Terminal Size           | 5mmø   |
| Terminal Torque         | 2.5Nm  |
| Terminal Capacity       | 4 x 2.5mm <sup>2</sup> or 2 x 4mm <sup>2</sup>   |
| Double Pole             | Yes  |
| Ingress Protection      | IP20   |
| Back Box Depth          | 25mm Minimum   |
| Operational Temperature | -5°C to +40°C  |
| Warranty                | 10 Years   |
| Standards               | BS 1363-2: 2016 +A1: 2018  |

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.