

## **Technical Specification**



Product Code: MD018SS Description: 13A/10AX Ingot Double Pole Switch Module





## **General Information**

Dimensions 25mm (W) x 53mm (H) x 20mm (D)

Aperture Dimensions 16mm (W) x 31.5mm (H)

Finish Stainless Steel

Materials Rocker Switch: Urea

Rear Housing: Nylon

Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Maximum Voltage 250V 50Hz

Load Rating 13A/10AX (Suitable For Inductive Loads)

Terminal Size 3.5mmø
Terminal Torque 0.4Nm

**Terminal Capacity** 4 x 1.5mm<sup>2</sup> or 2 x 2.5mm<sup>2</sup> **Back Box Depth** Dependent On Plate Used

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.