

## **Technical Specification**

CLICK® ScolmoregROUP

Product Code: DPBN722BK Description: 20A Ingot Double Pole Plate Switch





Representative Image

## **General Information**

 $\begin{tabular}{lll} \textbf{Dimensions} & & 88mm (W) \times 88mm (H) \times 8mm (D) \\ \begin{tabular}{lll} \textbf{Dimensions With Gasket} & & 91mm (W) \times 91mm (H) \times 9mm (D) \\ \end{tabular}$ 

Plate Design & Finish Rounded Profile Black Nickel

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel

Insert & Housing: Urea Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

 Load Rating
 20A

 Plate Fixing Centres
 60.3mm

 Terminal Size
 5mmø

 Terminal Torque
 1.8Nm

 Terminal Capacity
 4 x 2.5mm²

Double Pole Yes
Twin Earth Terminals Yes
Ingress Protection IP20

Back Box Depth 25mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.