

Technical Specification



Product Code: VPCH204WH Description: 45A 2 Gang Double Pole Switch With 13A Double Pole Switched Socket

Dutlet





Representative Image

General Information

 $\label{eq:definition} \textbf{Dimensions} \qquad 146 \text{mm (W)} \times 88 \text{mm (H)} \times 8 \text{mm (D)}$

Dimensions With Gasket 149mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Polished Chrome

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert, Switch & Rear Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

Maximum Voltage 250V∼ 50Hz

Load Rating 45A fixing Centres 120

 Plate Fixing Centres
 120.6mm

 Terminal Size
 6mmø

 Terminal Torque
 2.5Nm

 Terminal Capacity
 1 x 16mm²

Double Pole Yes
Twin Earth Terminals Yes
Ingress Protection IP20

Back Box Depth 35mm Minimum **Operational Temperature** -5°C to +40°C

Warranty 10 Years

Standards BS 4177:1992

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Technical Specification









SCP453BS

SCP453CH

SCP453SS





SCP453BK

SCP453PW