

Product Code: CT1016

Description: 230V 20A 16 Gang 4 Pole Lighting Management Box



General Information

Dimensions	264mm (W) x 269mm (H) x 69mm (D)
Material Composition	Front Plate & Back Box: Electrophoretically Coated Steel Male & Female Connectors: Nylon (PA66) Terminals: Silver Plated Brass Terminal Screws: Steel and Yellow Passivated Dust Covers: Polycarbonate
Maximum Voltage	230V~ 50Hz
Load Rating	20A
Ingress Protection	IP20
Operational Temperature	-5°C to +40°C
Warranty	10 Years

Compatible Connectors Input Connector: Input Connector: 3 Pole (CT203M) Connector Supplied
Output Connectors: Compatible with 3 and 4 Pole Male Connectors

Standards BS 8488 : 2009+ A1 :2010
EN 61535: 2009 + A1: 2013
BS 5733: 2010 + A1: 2014



Additional Information Ensure that the mains supply is isolated before commencing installation. Always refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Pre-fabricating wiring systems manufactured to BS 8488 by other manufacturers may not be compatible or safely inter-connectable with this system. Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.