

## **Technical Specification**



Product Code: DPSC500WH Description: 45A Ingot 1 Gang Double Pole Plate Switch





Representative Image

## **General Information**

 $\begin{array}{ccc} \textbf{Dimensions} & & 88\text{mm (W) x 88mm (H) x 8mm (D)} \\ \textbf{Dimensions With Gasket} & & 91\text{mm (W) x 91mm (H) x 9mm (D)} \\ \end{array}$ 

Plate Design & Finish Rounded Profile Satin Chrome

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert & Rear Housing: Urea Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 45A

Plate Fixing Centres 60.3mm
Terminal Size 6mmø
Terminal Torque 2.5Nm

Terminal Capacity 1 x 16mm²

Double Pole Yes

Twin Earth Terminals Yes

Ingress Protection IP20

Back Box Depth 35mm Minimum

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

## **Additional Information** Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.