

Technical Specification



Product Code: PRW024

Description: 20A Double Pole Sink/Bath Plate Switch With Neon





Representative Image

| General Information | |
|-------------------------|--|
| Dimensions | 86mm (W) x 86mm (H) x 11mm (D) |
| Plate Design & Finish | Square Edge Polar White |
| Materials | Front Plate & Rocker Switch: Urea Rear Housing: Urea Neon Lens: Polycarbonate Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel |
| Maximum Voltage | 250V~ 50Hz |
| Load Rating | 20A |
| Plate Fixing Centres | 60.3mm |
| Terminal Size | 5mmø |
| Terminal Torque | 1.8Nm |
| Terminal Capacity | 4 x 2.5mm ² |
| Double Pole | Yes |
| Twin Earth Terminals | Yes |
| Neon Indicator | Yes (Orange) |
| Ingress Protection | IP20 |
| Back Box Depth | 25mm Minimum |
| Operational Temperature | -5°C to +40°C |
| Warranty | 20 Years |
| Standards | BS EN 60669-1:1999 +A1:2002 +A2:2008 |
| Additional Information | Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae. |

Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E**: sales@scolmore.com | **W:** scolmore.com

Page 1 of 1 Rev.1.3 Errors & Omissions excluded. Specification is subject to change without notice.