

Product Code: FPBS502BK

Description: 45A Ingot 2 Gang (Vertica) Double Pole Plate Switch



Representative Image

General Information

| | |
|-------------------------|---|
| Dimensions | 88mm (W) x 146mm (H) x 1.3mm (D) |
| Dimensions With Gasket | 88mm (W) x 146mm (H) x 3mm (D) |
| Plate Design & Finish | Flat Plate Brushed Stainless |
| Insert Colour | Black |
| Materials | Front Plate: Stainless Steel Insert & Rear Housing: Urea Switch Cover: Stainless Steel Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel |
| Maximum Voltage | 250V~ 50Hz |
| Load Rating | 45A |
| Plate Fixing Centres | 60.3mm |
| Terminal Size | 6mmø |
| Terminal Torque | 2.5Nm |
| Terminal Capacity | 1 x 16mm ² |
| Double Pole | Yes |
| Twin Earth Terminals | Yes |
| Ingress Protection | IP20 |
| Back Box Depth | 47mm |
| Operational Temperature | -5°C to +40°C |
| Warranty | 10 Years |

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.