

Product Code: FPCH503BK

Description: 45A Ingot 2 Gang (Vertica) Double Pole Plate Switch With Neon



Representative Image

### General Information

|                                  |   |
|----------------------------------|---|
| <b>Dimensions</b>                | 88mm (W) x 146mm (H) x 1.3mm (D)  |
| <b>Dimensions With Gasket</b>    | 88mm (W) x 146mm (H) x 3mm (D)  |
| <b>Plate Design &amp; Finish</b> | Flat Plate Polished Chrome  |
| <b>Insert Colour</b>             | Black   |
| <b>Materials</b>                 | Front Plate: Stainless Steel<br>Insert & Rear Housing: Urea<br>Switch Cover: Stainless Steel<br>Neon Lens: Polycarbonate<br>Terminals: Brass<br>Terminal Screws: Steel & Yellow Passivated<br>Contacts: Silver "on-lay" Copper / Brass<br>Internal Busbars: Formed Pressed Brass<br>Earth Strap: Mild Steel |
| <b>Maximum Voltage</b>           | 250V~ 50Hz  |
| <b>Load Rating</b>               | 45A   |
| <b>Plate Fixing Centres</b>      | 120.6mm (Vertical Fixing)   |
| <b>Terminal Size</b>             | 6mmø  |
| <b>Terminal Torque</b>           | 2.5Nm   |
| <b>Terminal Capacity</b>         | 1 x 16mm <sup>2</sup>   |
| <b>Double Pole</b>               | Yes   |
| <b>Twin Earth Terminals</b>      | Yes   |
| <b>Neon Indicator</b>            | Yes (Red)   |
| <b>Ingress Protection</b>        | IP20  |
| <b>Back Box Depth</b>            | 47mm  |
| <b>Operational Temperature</b>   | -5°C to +40°C   |
| <b>Warranty</b>                  | 10 Years  |

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.