

Technical Specification



Product Code: SIN723BKSS Description: 20A Ingot Double Pole Plate Switch With Neon Insert





Representative Image

General Information

 $\textbf{Dimensions} \hspace{0.5in} 82.5 \text{mm (W)} \times 82.5 \text{mm (H)} \times 2.5 \text{mm (D)} \\$

Insert Finish Black Insert With Stainless Steel Switch

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar

White)

Materials Insert: Polycarbonate

Rear Housing: Urea

Switch Cover: Stainless Steel Neon Lens: Polycarbonate

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V~ 50Hz

Load Rating 20A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 1.8Nm
Terminal Censeity 4 x 2.5mm²

Terminal Capacity 4 x 2.5mm²

Double Pole Yes

Twin Earth Terminals Yes
Neon Indicator Yes (Red)
Ingress Protection IP20

Back Box Depth 35mm Minimum **Operational Temperature** -5°C to +40°C

Warranty 10 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Additional Information



Technical Specification



Product Code: SIN723BKSS Description: 20A Ingot Double Pole Plate Switch With Neon Insert

Compatible Cover Plates

Plate Dimensions 86mm (W) x 86mm (H) x 4mm (D)

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar

White

Materials: Decorative: Stainless Steel, Black & Polar White: Polycarbonate







SCP423CH



SCP423SS



SCP423BK



SCP423PW