

Technical Specification

CLICK® ScolmoreGROUP

Product Code: DPSC535WH Description: 13A Ingot 1 Gang Double Pole Switched Socket Outlet





Representative Image

General Information

 $\begin{tabular}{lll} \textbf{Dimensions} & & 88mm (W) \times 88mm (H) \times 8mm (D) \\ \begin{tabular}{lll} \textbf{Dimensions With Gasket} & & 91mm (W) \times 91mm (H) \times 9mm (D) \\ \end{tabular}$

Plate Design & Finish Rounded Profile Satin Chrome

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert & Housing: Urea Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 13A

Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 2.5Nm

Terminal Capacity 4 x 2.5mm² or 2 x 4mm²

Double Pole Yes
Ingress Protection IP20

Back Box Depth 25mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 1363-2: 2016 +A1: 2018

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.