

Product Code: CT203M

Description: 250V~ 20A 4 Pole Male (Fast-Fit Cable Clamps) Connector



General Information

Dimensions	73mm (W) x 50mm (D) x 25mm (H)
Material Composition	Cover: Polycarbonate Base & Terminal Housing: Nylon (PA66) Terminals: Silver Plated Brass Terminal Screws: Steel and Yellow Passivated
Maximum Voltage	250V~ 50Hz
Load Rating	20A
Rated Impulse Voltage	4kV
Terminal Capacity	3 x 2.5mm ² Max. T&E, 3 x 1.5mm ² Max. Flex
Termination Layout	A - N - E - L
Inner Core Strip Length	L & N: 35mm; E: 43mm
Conductor Strip Length	10mm
Cable Grip	Fast-Fit Cable Clamps
Cutout Required	Will pass through a 55mm round hole
Ingress Protection	IP20
Operational Temperature	-5°C to +40°C
Warranty	10 Years

Standards	EN 61535: 2009 + A1: 2013 BS 5733: 2010 + A1: 2014
------------------	---



Additional Information

Ensure that the mains supply is isolated before commencing installation. Always refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Any dangerous compatibility between different manufactures installation coupler systems is not automatically prevented by compliance with IEC 61535.

Product Code: CT203M

Description: 250V~ 20A 4 Pole Male (Fast-Fit Cable Clamps) Connector

Wiring Example

MALE - CT203M

FEMALE - CT203F

